

AUTOPACK / AUTOPACK HS

The AutoPack is the ultimate solution for automating bulk bag packing. Together, the SemiPack Bagger and Bag Placer combine into the AutoPack and can package from 25 to 100 pounds.

The AutoPack High Speed combines the SemiPack And the High Speed Bag Placer to increase speeds up to 20 bags per minute for 50 pound bags. This makes the AutoPack High Speed version an efficient machine for most bulk bagging applications.



FEATURES

- Automatic, wicketed, bulk bag packing
- Automatically stages bags to place under filling head
- Transforms two semi-automatic machines into an automatic bulk bagger system

ADDITIONAL OPTIONS

Left and right-hand versions available

WEIGHING PARTNERS

- MD14XL
- MD16
- MD16 D
- MD20 D
- M2i V
- M2 XXL

PACKAGE WEIGHT RANGE

AutoPack - 10 to 50 pounds

AutoPack HS - 10 to 100 pounds

PACKAGE DIMENSIONS

Paper

- Min. (Length + 2 x Width) 17.7"(450mm) x 18.9"(480mm) H
- Max. (Length + 2 x Width) 21.5"(545mm) x 40.6"(1030mm) H

Mesh

- Min. 17.7"(450mm) W x 22"(560mm) H
- Max. 24.4"(620mm) W x 45.3"(1150mm) H

Mesh w/ Closure

- Min. 17.7"(450mm) W x 22"(560mm) H
- Max. 24.4"(620mm) W x 45.3"(1150mm) H

(SemiPack HS) Mesh, Large (20-50lbs.)

- Min. 17.7"(450mm) W x 22"(560mm) H
- Max. 23.6"(600mm) W x 43.3"(1100mm) H

(SemiPack HS) Mesh, Small (10lbs.)

- Min. 12.4"(315mm) W x 22"(560mm) H
- Max. 15"(380mm) W x 43.3"(1100mm) H

CAPACITY / RATE

AUTOPACK

50 pounds at up to 15 bags per minute*

AUTOPACK HS

50 pounds at up to 20 bags per minute*

AIR CONSUMPTION

8 CFM**

POWER

230 Volt, 3 Phase and Ground

* Depends on product, infeed, and discharge system

** Actual air consumption will increase based on discharge system(s) chosen

AUTOPACK / AUTOPACK HS

