

M12 V

The M12 V has 12 V-shaped weighing buckets that open on two sides. With a low drop, the weight is directly applied to the discharge belt, giving you softer handling of your products. The M12 V is also optimized for high speeds with small weights, with a packing range from 1 to 50 pounds and rates up to 60 bags per minute. This makes it a fast and gentle weigher that can be used for many different produce types.

FEATURES

- 12 V-shaped bucket scales to weigh a variety of produce types and drop more gently onto the discharge belts
- High speed computer scans the weights available in all 12 buckets and chooses the best combination to provide the most accurate weight
- Strong, stable frame with vibration isolation
- Touchscreen computer
- Two computers for performing diagnostics or maintenance while also operating the weigher
- Operators can save packing styles in a user-friendly program for quick and easy changeovers
- Optional belts available versus vibrating lanes
- Optional router for remote assistance
- All product contact points are either stainless steel or plastic

DISCHARGE OPTIONS

- Stainless Steel, Single Discharge Belt
- Center Discharge Belt
- Combination Bucket

PARTNER OPTIONS

- Dual Wicket Bagger
- Carousel
- Clipper
- Rollstock Pouch Bagger
- Rollstock Poly Bagger
- Carton Filler
- Vertical Form, Fill & Seal



PACKAGE SIZE RANGE

1 to 50 pounds

CAPACITY / RATE

- 1 pound up to 60 bags per minute*
- 5 pounds up to 50 bags per minute*
- 10 pounds up to 30 bags per minute*
- 20 pounds up to 20 bags per minute*

AIR CONSUMPTION

6 CFM**

POWER

230 Volt, 3 Phase and Ground

MOST COMMON PRODUCTS

- Potatoes
- Onions
- Citrus Fruits
- Brussels Sprouts

Custom testing available for any product.

* Depends on product, infeed, and discharge system.

** Actual air consumption will increase based on discharge system(s) chosen.

M12 V

